



DESMOSOLVENT - SPECIAL SOLVENT FOR DILUTION AND CLEANING

DESMOSOLVENT is a diluent for DESMOPOL polyurethane membrane and TECNOTOP aliphatic resin topcoat. The dilution is only recommended by spray application ("airless equipment"). Also could be used for tools and equipment cleaning.

USES

- recommended as a diluent for the polyurethane membrane DESMOPOL, and the TECNOTOP 2C/2CP, aliphatic resins for spray applications (by roll or brush is not necessary)
- this is recommended to use for cleaning equipment and tools.

consumption	max. 5%
density at 23°C	0,869 ± 0,020 kg / l
color	transparent



PACKAGING

Metal tins of 25l.

SHELF LIFE

12 months at a temperature of 5 °C to 25 °C in dry sites.

HANDLING

These safety recommendations for handling, are necessary for the implementation process as well as in the pre and post, on exposure to the loading machinery.

- Respiratory Protection: When handling or spraying use an air-purifying respirator.
- Skin protection: Use rubber gloves, remove immediately after contamination. Wear clean body-covering. Wash thoroughly with soap and water after work and before eating, drinking or smoking.
- Eye / Face: Wear safety goggles to prevent splashing and exposure to particles in the air.
- Waste: Waste generation should be avoided or minimized. Incinerate under controlled conditions in accordance with local laws and national regulations.



Anyway, consult the material and safety data sheet (MSDS) of the product.



TECHNICAL DATA

PROPERTIES	VALUES
density at 23°C ISO 1675	0,869 ±0,020 kg /l
color	transparent
performance	±5% on DESMOPOL and TECNOTOP
flashpoint	27 °C
VOC (supplied)	869.9 g /l

NOTICE: While all the information presented in this document is believed to be reliable and to represent the best available data on these products, do not constitute sales specifications. The product properties may be changed without notice. NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE. IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE. Liability of Tecnopol Sistemas and its affiliates for all claims is limited to the purchase price of the material. Products may be toxic and require special precautions in handling. User should obtain detailed information on toxicity, together with proper shipping, handling and storage procedures, and comply with all applicable safety and environmental standards. No freedom from any patents or other industrial or intellectual property rights is granted or to be inferred.

