



PRICE LIST

APRIL 2022 v2

SALES CONDITIONS

- These terms and conditions are applied and an integral part of any contract of sale unless otherwise agreed between the parties forming it.
- Shipping in charge of the customer buyer, any risk or damage to goods will be assumed by him.
- Shipping which is the responsibility of TECNOPOL SISTEMAS SLU, risk and damage of goods, are assumed provide the following clauses:
 - Cracks, dents and defects observed during delivery time, shall be notified to the transport company before goods accepting and communicated in writing to TECNOPOL SISTEMAS SLU before 24h.
 - The delay in supplies behaves no compensation of any kind, either cancel the order once loaded the transport company.
- Returns will not be accepted unless previously agreed. All returns must be accepted by the company after product checking. The material and the product must be in perfect conditions. In any case, the customer must pay 10% of the value of the product delivered as regard unpacking and / or stock. It not will be accepted any material after one month from its delivery.
- In the event of non-conforming delivery, any complaint, whether it concerns the quantity or the quality of the materials sold, must be made in writing within 24 hours.
- Any tax or excise, of whatever nature, imposed on business operations and will be the responsibility of the buyer, although they were eventually required the seller.
- The amounts specified in this price list are all Ex Works
- The shipping always will be assumed by the buyer.
- For any legal matter arising from the sale or derived therefrom, the parties expressly submit to Barcelona Courts expressly waiving any other court.
- TECNOFLOOR: Special colourations: for orders over than 350 kg, we shipped the product already pigmented without additional cost. For orders, less than 350 kg colourant PIGMENTS EP will be delivered and billed separately. Check delivery times.
- TECNOTOP 2C / 2CP: Special colourations: for orders over than 350 kg, we will ship the product already pigmented without additional cost. For orders, less than 350 kg colourant PIGMENTS PU will be delivered and billed separately. Check delivery times.
- TECNOTOP 2C / 2CP can add an additive to get satin finish in orders over 300 kg, Check prices.
- TECNOTOP S-3000: Special colourations: for orders over than 450 kg, we will ship the product already pigmented without additional cost. For orders, less than 450 kg colourant PIGMENTS PU will be delivered and billed separately. Check delivery times.
- If not covered by these Sale Conditions, and subject to the following clause, TECNOPOL SISTEMAS SLU does not accept any liability beyond the remedies set forth herein, including but not limited to any liability for goods not being available for use, lost of profits or revenue or loss of business. Except as expressly provided herein, TECNOPOL SISTEMAS SLU will not be liable for any consequential, special, indirect, or punitive damages, even if advised of the possibility of such damages, or for any claim by any third party.
- The buyer of goods agrees that for any liability related to the purchase of goods, which shall be exclusively determined according to the above, TECNOPOL SISTEMAS SLU is not liable or responsible for any amount of damages above the amount of the relevant order, which shall be considered a maximum cap for all applicable concepts.
- Notwithstanding the above, nothing in these Sale Conditions shall limit or exclude TECNOPOL SISTEMAS SLU liability (i) for death or personal injury caused by gross negligence of TECNOPOL SISTEMAS SLU, (ii) for fraud or (iii) any liability which cannot be excluded by law.
- The remedies set forth in these Sale Conditions will be the buyer's sole and exclusive remedy for any claim against TECNOPOL SISTEMAS SLU under or related to these Sale Conditions.

Notes:

- VAT or other taxes are not included in this price list.
- This price list cancels any other previously issued.
- Prices and products on this price list may change and be applied without notice.
- Technical data and specified parameters of each product may be approximate. Always check the last version of technical data sheet or consult our technical department.
- The delivery times shall be defined from time to time, depending on the model, location and shipping type.

INDEX

TECNOCOAT pure hot-spray polyurea membranes

4

TECNOCOAT·H hybrid hot-spray polyurea membranes

7

DESMOPOL poliurethane membranes

8

TECNOTOP aliphatic top coats

10

TECNOFOAM polyurethane foams

12

TECNOFLOOR industrial flooring

16

PRIMER primers

18

Substrate preparation / Aggregates

20

Additives

22



tecnocoat

PURE HOT SPRAY COATINGS

WATERPROOFING

Pure polyurea liquid membranes



tecnocoat
P-2049



100% PURE POLYUREA MEMBRANE FOR WATERPROOFING AND PROTECTION.

Two-component, sprayable, aromatic coating suitable for waterproofing, protection and sealing. It is applied using specific spraying equipment and forms a solid, continuous, watertight and waterproof membrane, without joints or overlaps, with high mechanical qualities.

Packaging	American Pallet	Code A	Code B	Color	€/kg
60Kg (A)+60Kg (B)*	8(A) / 8(B)*	4TF9999976	4TF1539176	Grey	18,50 €
225Kg (A) + 225Kg (B)	4(A) / 4(B)*	4TF9999979	4TF1539179	Grey	17,20 €
			4TF1539079	White	
			4TF1539279	Black	
			4TF093079	Neutral	



Watch Video



For other colors, please consult your sales representative





DOWNLOAD DATA SHEET



100% PURE POLYUREA MEMBRANE, ELONGABLE (>600%)

Two-component, sprayable, aromatic coating, suitable for waterproofing, protection and sealing.


Specially designed for application on elements with structural movements. It is applied using specific spraying equipment and forms a solid, continuous, watertight and waterproof membrane without joints or overlaps.

Packaging	American Pallet	Code A	Code B	Color	€/kg
225Kg (A) + 225Kg (B)	4	4TB9999979	4TB1539179	 Grey	18,40 €
			4TB1539079	 White	
			4TB1539279	 Black	
			4TB1539579	 Dark Grey	


DOWNLOAD DATA SHEET

100% PURE POLYUREA MEMBRANE, WITH THERMAL INSULATION PROPERTIES



Two-component, sprayable, aromatic coating, suitable for waterproofing, protection and sealing. **This polyurea has a final expansion of 5 to 7 times its initial thickness.** It is applied using specific spraying equipment and forms a solid, continuous, watertight and waterproof membrane without joints or overlaps.

Packaging	American Pallet	Code A	Code B	Color	€/kg
225Kg (A) + 225Kg (B)	4(A) / 4(B)*	4TC9999979	4TC15392225	 Black	19,00 €


DOWNLOAD DATA SHEET

100% PURE POLYUREA MEMBRANE, LOW VISCOSITY


Two-component, sprayable, aromatic coating, suitable for waterproofing, protection and sealing. **It is designed as a coating and protection for TECNOFOAM polyurethane foam systems.** It is applied using specific spraying equipment and forms a solid, continuous, watertight and waterproof membrane, without joints or overlaps, with high mechanical qualities.

Packaging	American Pallet	Code A	Code B	Color	€/kg
60Kg (A) + 60Kg (B)*	8(A) / 8(B)*	4TG9999976	4TG1539176	 Grey	18,50 €
225Kg (A) + 225Kg (B)	4(A) / 4(B)*	4TG9999979	4TG1539179	 Grey	17,60 €


DOWNLOAD DATA SHEET

100% PURE POLYUREA MEMBRANE, HIGH STRENGTH

Two-component, sprayable, aromatic coating suitable for waterproofing, protection and sealing. **Designed for situations where chemical resistance is required.** It is applied using specific spraying equipment and forms a solid, continuous, watertight and waterproof membrane, without joints or overlaps, with high mechanical qualities.

Packaging	American Pallet	Code A	Code B	Color	€/kg
225Kg (A) + 225Kg (B)	4(A) / 4(B)*	4TK9999979	4TK1539179	 Grey	21,00 €


DOWNLOAD DATA SHEET




tecnocoat

P-2049 AS


100% PURE POLYUREA MEMBRANE, WITH ANTISTATIC PROPERTIES.

Two-component, sprayable, aromatic coating, suitable for waterproofing, protection and sealing. **Specific for applications where special anti-static properties are required.** It is applied using specific spraying equipment and forms a solid, continuous, watertight and waterproof membrane, without joints or overlaps, with high mechanical qualities.

0 VOC
EMISSIONS

DOWNLOAD
DATA SHEET



Packaging	American Pallet	Code A	Code B	Color	€/kg
225Kg (A) + 225Kg (B)	4(A) / 4(B)*	4TF9999979	3TA1539179	 Grey	19,50 €

COLD POLYUREA





tecnocoat

CP-2049

COLD HAND-APPLIED POLYUREA MEMBRANE FOR WATERPROOFING

Cold-applied liquid bi-component aromatic polyurea elastomer, which produces a continuous, elastic membrane, completely adhered to the substrate, without joints or overlaps, 100% watertight and waterproof, whose properties make it excellent for application on all types of surfaces, whether in new construction or rehabilitation. It is applied manually with a notched trowel, spreading it in a single layer.



Packaging	American Pallet	Code A	Code B	Color	€/kg
4,80Kg (A) + 0,20Kg (B)	120(A) / 400(B)*	4TA1539505	4TA9999905	 Dark Grey	15,30 €
19,20Kg (A) + 0,80Kg (B)	36(A) / 400(B)*	4TA1539520	4TA9999920	 Dark Grey	14,30 €

DOWNLOAD
DATA SHEET





WATERPROOFING

Hybrid polyurea liquid membranes



HYBRID POLYUREA MEMBRANE FOR WATERPROOFING AND COATING

Two-component, sprayable, aromatic coating, suitable for waterproofing, protection and sealing. It is applied using specific spraying equipment and forms a solid, continuous, watertight and waterproof membrane, without joints or overlaps, with high mechanical qualities.


Packaging	American Pallet	Code A	Code B	Color	€/kg
60Kg (A) + 60Kg (B)	8(A) / 8(B)*	4TF9999976	4TH1539160	 Grey	15,40 €
225Kg (A) + 225Kg (B)	4(A) / 4(B)*	4TF9999979	4TH1539179	 Grey	13,60 €

DOWNLOAD
DATA SHEET



HYBRID POLYUREA MEMBRANE, **STRETCHABLE**

Two-component, sprayable, aromatic coating, suitable for waterproofing, protection and sealing. Specially designed to be applied to **substrates with structural movements, where high elasticity is required.**


Packaging	American Pallet	Code A	Code B	Color	€/kg
225Kg (A) + 225Kg (B)	4(A) / 4(B)*	4TF9999979	4TL1539179	 Grey	15,10€

DOWNLOAD
DATA SHEET



HYBRID POLYUREA MEMBRANE, **LOW VISCOSITY**

Two-component, sprayable, aromatic coating suitable for waterproofing, protection and sealing. **Designed as a coating and protection for TECNOFOAM spray polyurethane foam systems**

Packaging	American Pallet	Code A	Code B	Color	€/kg
225Kg (A) + 225Kg (B)	4(A) / 4(B)*	4TG9999979	4TJ1539179	 Grey	14,00 €

DOWNLOAD
DATA SHEET





desmopol

LIQUID MEMBRANES

WATERPROOFING

Liquid membranes for cold application



SINGLE-COMPONENT POLYURETHANE WATERPROOFING MEMBRANE

Single component liquid made up of polyurethane, solvent-based, moisture-cured once catalyzed forms a continuous, seamless, solid and elastic, watertight, and waterproof membrane. Its properties make it an excellent choice to be applied on a multitude of substrates of new buildings and especially in refurbishments. It is applied manually, using a roller or brush, squeegee, and exceptionally, using specific spray equipment.

Packaging	American Pallet	Code	Color	€/kg
6 Kg	120	4TE1539006	White	10,40 €
		4TE1539106	Grey	
		4TE1556106	Red	
15 Kg	60	4TE1539015	White	9,80 €
		4TE1539115	Grey	
		4TE1556115	Red	
25 Kg	36	4TE1539025	White	9,20 €
		4TE1539125	Grey	
		4TE1556125	Red	



Watch Video

DOWNLOAD
DATA SHEET



TWO-COMPONENT, SOLVENT FREE, 100% SOLIDS, POLYURETHANE MEMBRANE WITH POTABLE WATER CONTACT CERTIFICATE

Two-component liquid made up of 100% solids aromatic polyurethane, thixotropic, which once catalyzed forms a continuous elastic membrane, without any joints, overlapping, or any integrated mesh needs. Its properties make it an excellent choice for achieving air-tightness and perfect waterproofing in potable water contact. It is applied manually, using a roller or brush.

Packaging	American Pallet	Code A	Code B	Color	€/kg
12,20 Kg (A) + 2,80 Kg (B)	60(A)/120(B)*	4TD1539015	4TD9999915	<input type="checkbox"/> White	17,00 €

DOWNLOAD
DATA SHEET



SINGLE COMPONENT, WATER-BASED TRANSPARENT AND ALIPHATIC POLYURETHANE WATERPROOFING MEMBRANE

High solid, transparent, glossy, and aliphatic polyurethane resin, which once made forms a continuous, elastic, without any joints or overlapping, and totally waterproof.

Packaging	American Pallet	Code	Color	€/kg
5 Kg	120	0191205	Transparent	36,80 €
20 Kg	36	0191220	Transparent	34,80 €

DOWNLOAD
DATA SHEET



SINGLE-COMPONENT, ALIPHATIC, WATERPROOFING ACRYLIC RESIN

Waterproofing and elastic coating based on polymer resins and pigments, forming a completely bonded sheet on the support without joints or overlaps.

Packaging	American Pallet	Code	Color	€/kg
6 Kg	120	4TS1539006	<input type="checkbox"/> White	8,30 €
		4TS1539106	<input type="checkbox"/> Grey	
		4TS1539305	<input checked="" type="checkbox"/> Red	
15 Kg	60	4TS1539015	<input type="checkbox"/> White	7,80 €
		4TS1539115	<input type="checkbox"/> Grey	
		4TS1539315	<input checked="" type="checkbox"/> Red	
25 Kg	36	4TS1539025	<input type="checkbox"/> White	7,30 €
		4TS1539125	<input type="checkbox"/> Grey	
		4TS1539325	<input checked="" type="checkbox"/> Red	

DOWNLOAD
DATA SHEET



SINGLE-COMPONENT, WATERPROOFING COATING WITH MODIFIED POLYURETHANE RESINS

Single-component elastic waterproofing coating based on water and modified polyurethane resins. Once dry, it forms a UV-resistant film that is fully adhered to the substrate, without joints or overlaps. The combination with polyurethane resins gives it a superior waterproofing capacity.

Packaging	American Pallet	Code	Color	€/kg
6 Kg	120	4TX1539006	<input type="checkbox"/> White	9,45 €
15 Kg	60	4TX1539015	<input type="checkbox"/> Blanco	8,90 €
25 Kg	36	4TX1539025	<input type="checkbox"/> Blanco	8,60 €

DOWNLOAD
DATA SHEET









ALIPHATIC PROTECTION AND FLOORING

UV-resistant resins and coatings



SINGLE COMPONENT, COLORED, ALIPHATIC RESIN TO PROTECT AGAINST UV RAYS

Resin for treatment, decoration, and protection of flooring finishing. It forms a continuous film with excellent adhesion and mechanical properties. It is resistant to weathering, extreme temperatures, and UV radiation.

Packaging	American Pallet	Code	Color	€/kg
5 Kg	120	4TM218105	 White (RAL 9010)	23,00 €
		4TM214905	 Grey (RAL 7042)	
		4TM216005	 Red (RAL 8004)	
20 Kg	36	4TM218120	 White (RAL 9010)	21,00 €
		4TM214920	 Grey (RAL 7042)	
		4TM216020	 Red (RAL 8004)	



Other RAL see conditions of sale page

**DOWNLOAD
DATA SHEET**



TWO-COMPONENT, ALIPHATIC POLYURETHANE RESIN, AS A FLOORING AND PROTECTION AGAINST UV RAYS

Colored solvent-based polyurethane resin for coating, decoration and protection of floorings with glossy finish as well as protection of aromatic membranes against UV rays. Resistant to vehicular traffic.

Packaging	American Pallet	Code A	Code B	Color	€/kg
4,30 kg (A) + 0,70 Kg (B)	120(A) 400(B)*	4TN093005	4TN9999905	<input type="checkbox"/> Neutral	25,50 €
		4TN214905		<input type="checkbox"/> Grey (RAL 7042)	
		4TN1539305		<input type="checkbox"/> Red (RAL 8004)	
17,20 kg (A) + 2,80 Kg (B)	36(A) 120(B)*	4TN093020	4TN9999920	<input type="checkbox"/> Neutral	24,50 €
		4TN214920		<input type="checkbox"/> Grey (RAL 7042)	
		4TN1539320		<input type="checkbox"/> Red (RAL 8004)	



Other RAL see conditions of sale page



TWO-COMPONENT POLYURETHANE RESIN, FOR TOTAL IMMERSION IN CHLORINATED OR SALT WATER AND PROTECTION AGAINST UV RAYS

Coloured resin for coating and decoration, especially on surfaces in contact with chlorinated water, saline water and total immersion situations, as well as protection of aromatic membranes against UV rays.

Packaging	American Pallet	Code A	Code B	Color	€/kg
4,30 kg (A) + 0,70 Kg (B)	120(A) 400(B)*	4TP093005	4TN9999905	<input type="checkbox"/> Neutral	28,00 €
		4TP1539005		<input type="checkbox"/> White (RAL 9003)	
		4TP207005		<input type="checkbox"/> Blue (RAL 5012)	
17,20 kg (A) + 2,80 Kg (B)	36(A) 120(B)*	4TP093020	4TN9999920	<input type="checkbox"/> Neutral	27,00 €
		4TP1539020		<input type="checkbox"/> White (RAL 9003)	
		4TP207020		<input type="checkbox"/> Blue (RAL 5012)	



Other RAL see conditions of sale page



TWO COMPONENT, HI-TECH COLORED, COLD POLYUREA BASED RESIN FOR HIGH QUALITY COATINGS

Two-component, fluid, polyurea-based coating, with very high mechanical resistance, flexibility, with a fast drying process and manual cold application. High performance in resistance to vehicular traffic.

Packaging	American Pallet	Code A	Code B	Color	€/kg
4 kg (A) + 1 Kg (B)	120(A) 400(B)*	4TR093005	4TR9999905	<input type="checkbox"/> Neutral	40,00 €
		4TR214920		<input type="checkbox"/> Grey	
16 kg (A) + 4 Kg (B)	36(A) 120(B)*	4TR093020	4TR9999920	<input type="checkbox"/> Neutral	39,00 €
		4TR214920AN		<input type="checkbox"/> Grey	



Other RAL see conditions of sale page



HIGH QUALITY, HIGH STRENGTH, HIGH DURABILITY ALIPHATIC TRANSPARENT COATING

Two-component, fluid, polyurea-based coating with very high mechanical resistance, flexibility, with a fast drying process and manual cold application. For both indoor and outdoor surfaces.

Packaging	American Pallet	Code A	Code B	Color	€/kg
1,40 kg (A) + 3,60 Kg (B)	216(A) 120(B)*	4TR092005	4TR9999805	Transparent	45,00 €



Watch Video





WATER AS AN EXPANSION AGENT

FREE FROM CONTAMINATING GREENHOUSE EFFECT GAS EMISSIONS


The most ECO- friendly TECNOFOAM range using WATER as an blowing agent, which is free from gases toxic to the environment.

In addition, water-based TECNOFOAM provides completely stable and inert systems, without the emission of any toxic particles, either during the application process or for the length of its useful life.

The thermal conductivity remains stable from the moment of application, generating layers with a high dimensional stability.



tecnofoam
G-2008 H2O



Packaging	American Pallet	Code A	Code B	Color	€/kg
250 kg (A) + 215 Kg (B)	4(A)/4(B)*	2447979	2447878	Yellow	Weekly quotation



Watch Video

DOWNLOAD DATA SHEET




tecnofoam
G-2025 H2O




Packaging	American Pallet	Code A	Code B	Color	€/kg
250 kg (A) + 240 Kg (B)	4(A)/4(B)*	2447979	3TS1556278	Salmon	Weekly quotation
		2447979	3TS1556378	Green	

DOWNLOAD DATA SHEET







Packaging	American Pallet	Code A	Code B	Color	€/kg
250 kg (A) + 240 Kg (B)	4(A)/4(B)*	2447979	3TT1556278	Salmon	Weekly quotation
		2447979	3TT1556378	Green	



Packaging	American Pallet	Code A	Code B	Color	€/kg
250 kg (A) + 240 Kg (B)	4(A)/4(B)*	2447979	3TU1556278	Salmon	Weekly quotation
		2447979	3TU1556378	Green	



Packaging	American Pallet	Code A	Code B	Color	€/kg
250 kg (A) + 240 Kg (B)	4(A)/4(B)*	2447979	3TV1556278	Salmon	Weekly quotation
		2447979	3TV1556378	Green	



Packaging	American Pallet	Code A	Code B	Color	€/kg
250 kg (A) + 240 Kg (B)	4(A)/4(B)*	2447979	3TW1556278	Salmon	Weekly quotation
		2447979	3TW1556378	Green	





tecnofoam HFO

CLOSED CELL POLYURETHANE FOAMS

TECNOFOAM HFO RANGE

CLOSED-CELL EXPANSION ENERGY

Systems with a high closed-cell content provide excellent resistance to water vapour absorption, which translates into better waterproofing of the building element, whether the roof or facade. In addition, the high reactivity of the gas enables application in all climates, with great advantages particularly in cold environments.

TECNOFOAM HFO complies with environmental regulations for the emission of fluoride gases in the European Union.

1
GWP

0
ODP



tecnofoam
G-2035 HFO

density
34~38
kg/m³

conductivity
0,022
W/m·K

closed cell
>95%
(CCC4)

fire reaction
Euroclass
E

Packaging	American Pallet	Code A	Code B	Color	€/kg
250 kg (A) + 230 Kg (B)	4(A)/4(B)*	2447979	2448379	Yellow	Weekly quotation

DOWNLOAD
DATA SHEET



tecnofoam
G-2040 HFO

density
40~46
kg/m³

conductivity
0,022
W/m·K


closed cell
>95%
(CCC4)

fire reaction
Euroclass
E

Packaging	American Pallet	Code A	Code B	Color	€/kg
250 kg (A) + 230 Kg (B)	4(A)/4(B)*	2447979	2448679	Yellow	Weekly quotation

DOWNLOAD
DATA SHEET






Packaging	American Pallet	Code A	Code B	Color	€/kg
250 kg (A) + 230 Kg (B)	4(A)/4(B)*	2447979	2448879	Yellow	Weekly quotation





TECNOFOAM INJECTION

INSULATION WHICH REACHES INTO ALL THE CORNERS

The TECNOFOAM injection systems are specially formulated for applications which require a continual injected thermal insulation system. Suitable for both construction and industrial installations in general and available in two densities: 15 and 35 kg/m³.



Packaging	American Pallet	Code A	Code B	Color	€/kg
50 kg (A) + 50 Kg (B)	8(A)/8(B)*	2447950	2446850	Yellow	Weekly quotation
250 kg (A) + 220 Kg (B)	4(A)/4(B)*	2447979	2446879	Yellow	



Packaging	American Pallet	Code A	Code B	Color	€/kg
250 kg (A) + 230 Kg (B)	4(A)/4(B)*	2447979	2448979	Yellow	Weekly quotation





tecnofloor

FLOORING SYSTEMS

FLOORING

Continuous industrial flooring






tecnofloor

T-3020

100% SOLIDS EPOXY RESIN FOR SURFACING AND FLOORING

Two-component, pigmented, flowable, glossy, epoxy-based coating with high chemical and mechanical resistance, forming a continuous, aromatic coating. For the coating and covering of surfaces for pedestrian and vehicular traffic as well as for industrial applications.

Packaging	American Pallet	Code A	Code B	Color	€/kg
20,60 kg (A) + 4,40 Kg (B)	36(A) 120(B)*	4TT214925	4TT9999925	 Grey (RAL 7042)	17,80 €
		4TT203925		 Red (RAL 3016)	
		4TT210725		 Green (RAL 6024)	



Other RAL minimum
350 kg comp. A (17 kits)

**DOWNLOAD
DATA SHEET**



tecnofloor

T-3020 / N

100% SOLID & NEUTRAL EPOXY RESIN FOR COATING & FLOORING

Same characteristics as Tecnofloor T-3020 but in a neutral version to be pigmented with the PIGMENTS EP range.





Packaging	American Pallet	Code A	Code B	Color	€/kg
18.6 Kg (A) + 4,40 Kg (B)	36(A) 120(B)*	4TT093023	4TT9999925	Neutral	17,00 €

**DOWNLOAD
DATA SHEET**



WATER-BASED EPOXY RESIN FOR SURFACING AND FLOORING

Two-component, pigmented, flowable, water-based epoxy coating that forms a continuous, aromatic coating. With medium chemical and mechanical resistance, suitable as a finish for industrial flooring and road traffic. It is certified for migration to drinking water and food contact, in addition to the European standard for the protection of structural concrete.

Packaging	Uds./ Palet Americano	Code A	Code B	Color	€/kg
4 Kg (A) + 1 Kg (B)	120(A) 400(B)*	4TW214905	4TW9999905	 Grey (RAL 7042)	17,60 €
		4TW208505		 Green (RAL 6001)	
20 Kg (A) + 5 Kg (B)	36(A) 120(B)*	4TW214925	4TW9999925	 Grey (RAL 7042)	17,00 €
		4TW208525		 Green (RAL 6001)	





Other RAL minimum 350 kg comp. A (18 large kits)

[DOWNLOAD DATA SHEET](#)


100% SOLIDS POLYURETHANE RESIN FOR SURFACING AND FLOORING

Two-component, pigmented, glossy, flowable, 100% solids polyurethane based coating with chemical and mechanical resistance that forms a continuous, aromatic coating. For the coating and covering of surfaces for pedestrian and vehicular traffic.

Packaging	American Pallet	Code A	Code B	Color	€/kg
3,9 Kg (A) + 1,1 Kg (B)	120(A) 400(B)*	4TU214905	4TU9999905	 Grey (RAL 7042)	16,50 €
19,5 Kg (A) + 5,5 Kg (B)	36(A) 120(B)*	4TU214925	4TU9999925	 Grey (RAL 7042)	15,90 €




Other RAL minimum 350 kg comp. A (18 large kits)

[DOWNLOAD DATA SHEET](#)


TWO-COMPONENT, ALIPHATIC, TRANSPARENT BINDER, POLYURETHANE BASED, FOR DECORATIVE USE WITH AGGREGATES

Two-component polyurethane, aliphatic, odourless, Transparent, 100% solids to be used as a binder suitable as stone encapsulation for pedestrian and vehicular traffic areas exposed to UV rays.

Packaging	American Pallet	Code A	Code B	Color	€/kg
2,5 Kg (A) + 4,5 Kg (B)	108(A) 48(B)*	0461607	0461707	 Transparent	25,00 €

[DOWNLOAD DATA SHEET](#)


CURING ACCELERATOR FOR TECNOFLOOR STF-7020

Single-component yellowish additive that reduces the pot-life, the drying time and the in-service times of the Tecnofloor STF-7020 resin binder. The mixing ratio is carried out at a maximum consumption of 150 g / 7 kg of Tecnofloor STF-7020 kit.

Packaging	American Pallet	Code	€/l
450 ml	N/D	N/D	43,10 €

[DOWNLOAD DATA SHEET](#)


PRIMER RANGE

Maximise adhesion to any substrate



SINGLE-COMPONENT, SOLVENT BASED, POLYURETHANE RESIN

Single-component polyurethane resin with low viscosity and high solids content.

Packaging	American Pallet	Code	€/kg
5 Kg	120	1047105	18,00 €
20 Kg	36	1047120	17,00 €



TWO-COMPONENT 100% SOLIDS POLYURETHANE PRIMER

Designed to increase adhesion and improve the flatness of rough substrates (structural concretes, mortars, ...)

Packaging	American Pallet	Code A	Code B	€/kg
5 Kg (A) + 5 Kg (B)	120(A) / 120(B)*	0192710	0192610	24,00 €



TWO-COMPONENT 100% SOLIDS POLYURETHANE PRIMER FOR LOW TEMPERATURES

Same characteristics as PRIMER PU-1050 but for low ambient temperature situations.

Packaging	American Pallet	Code A	Code B	€/kg
5 Kg (A) + 5 Kg (B)	120(A) / 120(B)*	0192710	0192905	24,50 €



TWO-COMPONENT 100% SOLIDS EPOXY RESIN AND FILLERS

Designed for levelling concrete, mortar or ceramic substrates and increasing adhesion.

Packaging	American Pallet	Code A	Code B	€/kg
16 Kg (A) + 4 Kg (B)	36(A) / 120(B)*	0182020	0182220	18,00 €





TWO-COMPONENT 100% SOLIDS EPOXY RESIN

Designed for levelling concrete, mortar or ceramic substrates and increasing adhesion.

Packaging	American Pallet	Code A	Code B	€/kg
10,3 Kg (A) + 4,7 Kg (B)	36(A) / 120(B)*	0191415	0191515	24,00 €



TWO-COMPONENT 100% SOLIDS EPOXY RESIN

Designed to increase adhesion on non-porous substrates such as metal.

Packaging	American Pallet	Code A	Code B	€/kg
8 Kg (A) + 5 Kg (B)	36(A) / 120(B)*	0193713	0193813	27,00 €



TWO-COMPONENT WATER BASED EPOXY RESIN

Resin with 0% volatile matter. Designed to increase the adhesion of rough substrates.

Packaging	American Pallet	Code A	Code B	€/kg
3 Kg (A) + 1 Kg (B)	120(A) / 400(B)*	0192304	0192404	23,00 €
15 Kg (A) + 5 Kg (B)	36(A) / 120(B)*	0192320	0192420	21,00 €



TWO-COMPONENT 100% SOLIDS EPOXY RESIN FOR HIGH MOISTURE CONTENT SUBSTRATES

Solvent-free, low viscosity resin for use on porous substrates with high humidity (up to 98%).

Packaging	American Pallet	Code A	Code B	€/kg
11,95 Kg (A) + 3,05 Kg (B)	60(A) / 120(B)*	0193215AN	0193315AN	27,00 €



TWO-COMPONENT FAST DRYING 100% SOLID EPOXY RESIN FOR HIGH MOISTURE SUBSTRATES

Solvent-free, low viscosity, fast drying resin, applicable on porous substrates with high humidity (up to 98%).

Packaging	American Pallet	Code A	Code B	€/kg
11,95 Kg (A) + 3,05 Kg (B)	60(A) / 120(B)*	0193215AN	0193515AN	28,00 €



IMPREGNATION IN ALCOHOLIC SOLUTION CONTAINING ADHESION PROMOTERS

Colourless impregnation to increase the adhesion of DESMOPOL T and TECNOTOP S-3000 T on non-porous substrates.

Packaging	American Pallet	Code	€/kg
4 Kg	120	0193604	26,00 €



* Parts on separate pallets

SUBSTRATE PREPARATION



POLYURETHANE MASTIC

Single component polyurethane mastic that cures rapidly on contact with atmospheric moisture, forming a hard sealant, elastic and of a medium-high elasticity modulus. For sealing of vertical and horizontal joints.

Packaging	European Pallet	Code	Color	€/u
600 cm ³	720	0106156	Grey	11,00 €



POLYUREA MASTIC

Two-component polyurea mastic, high solids content, rapid cure and UV resistant. For filling control joints and cracks on concrete floors.

Packaging	American Pallet	Code A	Code B	Color	€/kg
20 kg (A) + 20 Kg (B)	36(A) / 36(B)*	3TM999920	3TM1539120	Grey	21,00€
60 kg (A) + 60 Kg (B)	10(A) / 10(B)*	3TM999960	3TM1539160	Grey	19,00€



GEOTEXTILE REINFORCEMENT BAND

A transversely deformable adhesive band, formed of a viscous-elastic layer coated on a nonwoven mesh. The nonwoven element allows adaptation to the support of the band and is highly recommended for specific applications of polyurea membranes.

Packaging	American Pallet	Code	€/m
Roll 15 m	216	7955115	5,00 €



REINFORCING FIBER-GLASS MESH

Mesh for reinforcing for the polyurethane waterproofing membranes Desmopol / Desmopol CB at detail work, critical points, and general areas in case of was necessary.

Packaging	American Pallet	Code	€/u
Roll 50m x 1m	64	2815950	140,00 €



POLYPROPYLENE MESH

Non-woven mesh made of 100% polypropylene fibers, heat-set on one side, and calendered on the other, with a mass of 200 g/m², offered in rolls. Is a specific material to be used in Tecnocoat application where the substrate is very irregular or on the soil.

Packaging	American Pallet	Code	€/u
Roll 70m x 1.5m	16	2815870	300,00 €



THREE-COMPONENT EPOXY-CEMENTITIOUS THIXOTROPIC MORTAR FOR SMOOTHING OFF DAMP SUBSTRATES

Tri-component mortar for protecting and smoothing vertical and horizontal concrete surfaces subject to moisture. It meets the requirements defined by EN 1504-9 ("Products and systems for the protection and repair of concrete structures - Definitions, requirements, quality control and conformity assessment - General principles for the use of products and systems") and the minimum requirements of EN 1504-2 (C) coating according to MC and IR principles ("Surface protection systems for concrete").

Packaging	American Pallet	Code A	Code B	Code C	€/Kg
1,5kg (A) +4,75Kg (B) +25kg (C)	198(A) / 128(B) / 50(C)*	135331TEC	135431TEC	135531TEC	9,70 €

[DOWNLOAD
DATA SHEET](#)


FILLERS



ANTISLIP AGGREGATES FOR ANTISLIP FINISH

Charges /aggregates for anti-slip finishes. Used for DESMOPOL, TECNOCOAT waterproofing, coating liquid systems, and for TECNOFLOOR and TECNOTOP flooring systems in multilayer pavement systems.

Packaging	American Pallet	Code	€/Kg
25 Kg	50	1599125	1,20€

[DOWNLOAD
DATA SHEET](#)


PLASTIC CHARGES FOR ANTISLIP FINISH

TECNOPLASTIC F is a kind of micronized plastic (polyamide) for texturing polyurethane resins, and achieve antislip surfaces for flooring.

Packaging	American Pallet	Code	€/Kg
2 Kg	120	0199402	46,00 €

[DOWNLOAD
DATA SHEET](#)


PLASTIC CHARGES FOR ANTISLIP FINISH

TECNOPLASTIC C is a kind of plastic (polyamide) micronized specially selected for texturing finishing resins, and thus achieve antislip floor finish, especially in situations of vehicular traffic.

Packaging	American Pallet	Code	€/kg
2 Kg	120	0199202	69,00 €

[DOWNLOAD
DATA SHEET](#)


ADDITIVES



ADDITIVE FOR THE APPLICATION OF DESMOPOL IN JUST ONE COAT

DESMOPLUS is an additive that gives to the single component polyurethane membrane DESMOPOL several properties to facilitate its application in one layer without bubbles inside, improve their physical and mechanical properties, and gives a fast dry time. It is suitable for the application of polyurethane membranes in low-temperature conditions or adverse weather conditions.

Packaging	American Pallet	Code	€/l
0,50 l	400	0191155	28,00 €
1,20 l	400	0191101	24,00 €
2 l	216	0191102	22,00 €



Watch Video

DOWNLOAD DATA SHEET



ADDITIVE FOR MEMBRANE APPLICATION DESMOPOL IN A SINGLE COAT IN WARM ENVIRONMENTS

DESMOPLUS 700 has a higher pot-life than DESMOPLUS, which makes it suitable for use in warm environments. It facilitates the application of DESMOPOL in a single layer without internal bubbling, improving the physical-mechanical properties and the speed of initial drying.

Packaging	American Pallet	Code	€/l
1,20 l	400	0190401	24,00 €
2 l	216	0190402	22,00 €

DOWNLOAD DATA SHEET



SPECIAL SOLVENT FOR DILUTION OR CLEANING

Thinner for the DESMOPOL polyurethane membrane and the TECNOTOP range of aliphatic varnishes, for dilution in application with equipment and for use in the cleaning of spraying tools and machinery.

Packaging	American Pallet	Code	€/kg
25 Kg	36	1048525	6,40 €

DOWNLOAD DATA SHEET



THICKENER RHEOLOGY MODIFIER FOR DESMOPOL

Thixotropic additive specially designed to be mixed with DESMOPOL polyurethane liquid membranes, giving them thixotropic properties for their application on vertical or inclined surfaces, thus preventing the membrane from dropping.

Packaging	American Pallet	Code	€/kg
1 l	400	0191301	44,00 €

DOWNLOAD DATA SHEET





CLEANING SOLVENT FOR SPRAYING EQUIPMENT

Cleaning solvent for polyurea (Tecnocoat) and polyurethane foam (Tecnofoam) spraying equipment. Specified for cleaning parts exposed to contact with amines, polyols or isocyanates.

Packaging	American Pallet	Code	€/l
25 l	36	1083525	11,40 €

DOWNLOAD
DATA SHEET



PLASTICISER OIL

Plasticising oil used for the preservation and protection of the inside of polyurethane (PU) or polyurea (PUA) foam spraying equipment parts, such as the inside of hoses.

Packaging	American Pallet	Code	€/l
25 l	36	1083625	16,00 €

DOWNLOAD
DATA SHEET



SPECIAL PIGMENTS FOR TECNOFLOOR T-3020 N

PIGMENTS EP is a pigment paste for the pigmentation of our TECNOFLOOR T-3020 N epoxy resins, to be mixed with neutral epoxy resins to achieve the final colouring according to RAL CHART desired by the user.

Packaging	American Pallet	Color	€/kg
2 Kg	120	RAL CHART	44,00 €

DOWNLOAD
DATA SHEET



SPECIAL PIGMENTS FOR TECNOTOP RESIN RANGE(NEUTRAL VERSION)

PIGMENTS PU is a pigment paste for the pigmentation of our aliphatic resins TECNOTOP S-3000/2C/2CP and TECNOFLOOR PU-3060 (in neutral versions). These resins are originally translucent and can be coloured by the user according to a RAL CHART.

Packaging	American Pallet	Color	€/u
1 Kg	400	RAL CHART	44,00 €

DOWNLOAD
DATA SHEET





TECNOPOL C/. Finlàndia, 33
08520 Les Franqueses del Vallès · Barcelona (Spain)
(+34) 93 568 21 11 · info@tecnopol.es · www.tecnopolgroup.com